

C € 0085



CERT

EU type examination certificate

EU-Baumusterprüfbescheinigung

CE-0085DL0067

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	InterApp-Valcom S.A. Calderon de la Barca, 12/14, E-28860 Paracuellos de Jarama (Madrid)
Distributor <i>Vertreiber</i>	InterApp-Valcom S.A. Calderon de la Barca, 12/14, E-28860 Paracuellos de Jarama (Madrid)
Product Category <i>Produktart</i>	Gas fittings: Shut-off valve, magnetic/ motor/ pneumatic operated (4307)
Product description <i>Produktbezeichnung</i>	pneumatic operated automatic shut-off valve
Model <i>Modell</i>	Desponia, Desponia plus
Countries of Destination <i>Bestimmungsländer</i>	AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR
Test reports <i>Prüfberichte</i>	Type testing: 19-00310-177 from 30.12.2019 (EBI) Type testing: 20-00317-AB02-177 from 24.08.2023 (EBI)
Test basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 161 (01.04.2013)

Date of Expiry / File No. 31.03.2030 / 23-0489-GEA
Ablaufdatum / AZ



09.02.2024 Pz A-1/2

i.A. W. Z.

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH - notified by the government of the Federal Republic of Germany and officially registered by the European Commission for conformity assessment of gas appliances

DVGW CERT GmbH – von der Deutschen Bundesregierung benannte und von der Europäischen Kommission offiziell registrierte Stelle für die Konformitätsbewertung von Gasgeräten

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888

Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
Desponia, Desponia plus	Nominal diameter: DN 50 Max. operating pressure: 5 bar	
Desponia, Desponia plus	Nominal diameter: DN 65 Max. operating pressure: 5 bar	
Desponia, Desponia plus	Nominal diameter: DN 80 Max. operating pressure: 5 bar	
Desponia, Desponia plus	Nominal diameter: DN 100 Max. operating pressure: 5 bar	
Desponia, Desponia plus	Nominal diameter: DN 125 Max. operating pressure: 5 bar	
Desponia, Desponia plus	Nominal diameter: DN 150 Max. operating pressure: 5 bar	
Desponia, Desponia plus	Nominal diameter: DN 200 Max. operating pressure: 5 bar	
Desponia, Desponia plus	Nominal diameter: DN 250 Max. operating pressure: 5 bar	

Hints of Utilization /Remarks

Verwendungshinweise / Bemerkungen

valve class: A (with solenoidvalve 331N03.... and VSNC...)

ambient temperature range: -20...+60 °C (with solenoidvalve VSNC...; temperatur range 0...60°C)

connection: ends for clamping-connection for the installation between flanges according to DIN EN 1092